

Overview Features Specifications Models and Accessories Knowledge and Information

Specifications	
Diameter of measurable conductor	0.12" or 30.5 mm max
Operating temperature	-14 to 122°F (-10 to 50°C)
Storage Temperature	-40 to 140°F (-40 to 60°C)
Operating Humidity	< 90% @ <30 °C, < 75% @ 30 to 55°C
Operating Altitude	0 to 2500 m
IP Rating	IP 40
Size	240 x 80 x 44 mm, (9.375 x 3.125 x 1.625 in.)
Weight	310G, (11 oz.)
Vibration	Random 2 g, 5 to 500 Hz
Shock	1 meter drop test (except the jaw)
EMI/RFI	Meets EN61326-1
Temperature Coefficient	0.01% °C (<18? or > 28?)
Power, battery life	(2) AA 1.5 V Alkaline, IEC 1010-2-031,150 hours typical Automatic low battery indicator
Warranty	Three years for electronics One year for cable and clamp assembly

Clamp Meter | Current Meters | DC Clamp Meters | HVAC Clamp Meter



Where to buy clamp meters » Clamp meter selector tool » Clamp meter application notes and

Clamp meter virtual demos » Clamp meter accessories » Process tools mA clamp meter ROI

case studies »

Follow us 🚮 😉 🝱 🔟 Home | Site Map | Fluke Corporation | Safety Notices | Terms and Conditions | Privacy Statement | Disclaimer © 1995 – 2010 Fluke Corporation