

Cx (pF)		WORKING VOLTAGE -40°C TO +125°C		I _{DC}		D.W.V.		I.R. MIN.		TYPICAL NO LOAD INSERTION LOSS (dB) AT 25°C PER MIL-STD-220			
12,000/27,000		150 VDC		30 Amps		2121 VDC (60 SEC.)		10 G Ω		10 MHz		100 MHz	
										28		45	
										1 GHz		10 GHz	
										70		70	

REVISION RECORD Original Release C.O. 20030718-1-03 Cx WAS 15,000 MIN. S.M. 08-24-05 20050818-12-21 ADDED NOTES 1-4 & RE-NUMBERED.S.M. 09-29-05 20050922-1-10 Cx WAS 12,000/18,000. S.M. 10-19-05 20051006-3-03 NOTE 4 REVISED. ADDED INK DOT. REVISED TORQUE. S.M. 01-23-06 20060103-1-09 DIA .190 NOTE WAS 2. S.M. 01-11-07 20070109-2-01		TOLERANCES unless otherwise specified		Title "C" FEED - THRU TERMINAL BLOCK 2 POSITION (UL RECOGNIZED)	
		2 PLC. DECIMAL ± N/A			
		3 PLC. DECIMAL ± .030 [0.76]			
		ANGLES ± N/A			
		TUSONIX TUCSON, ARIZONA		Drawn S.M. 07-31-03 Scale FULL	
		Approved R.C. 07-31-03		A 7602-602	