



Wire Cutters, Round, Tapered, Angulated by EXCELTA Tapered-Relieved Head Cutters

7234E ★★★★★ Cutter - Tapered Head

4 3/4" Five Star***** Tapered Head maximum flush cut. Made in the U.S.A. Cutting range 20 AWG (.032") to 30 AWG (.010") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell.



 [Click to Enlarge](#)

7144E ★★★★★ Cutter - Tapered Head - Maximum Flush

5 7/8" Five Star***** Tapered Head maximum flush cutter. Made in the U.S.A. The 7100 series cutters have 1" longer Ergonomic handles and ESD safe foam cushion grips, stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell. Cutting range 18 AWG (.040") to 36 AWG (.005") soft copper leads and wires. Length: 5.5
Cut: Maximum Flush



 [Click to Enlarge](#)

7244E ★★★★★ Cutter - Tapered Head - Maximum Flush

4 7/8" Five Star***** Tapered Head flush cutter. Made in the U.S.A. Cutting range 18 AWG (.040") to 30 AWG (.010") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell
Length: 5
Cut: Maximum Flush



 [Click to Enlarge](#)

77EI ★★★★★

Cutter - Tapered Head - Maximum Flush

4" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 24 to 32 gauge. (.020" to .008")

Length: 4

Cut: Maximum Flush



[Click to Enlarge](#)

86EI-4.75 ★★★★★

Cutter - Tapered Head - Maximum Flush

4 3/4" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 18 to 30 gauge. (.040" to .010")

Length: 4.75

Cut: Maximum Flush



[Click to Enlarge](#)

86EI-5 ★★★★★

Cutter - Tapered Head - Maximum Flush

5" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 18 to 26 gauge. (.040" to .016")

Length: 5

Cut: Maximum Flush



[Click to Enlarge](#)

86EI-6 ★★★★★

Cutter - Tapered Head - Maximum Flush

6" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 14 to 24 gauge. (.064" to .020")

Length: 6.25

Cut: Maximum Flush



[Click to Enlarge](#)

95EI ★★★★★

Cutter - Tapered Head - Maximum Flush

4 1/4" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 20 to 28 gauge. (.032" to .012")

Length: 4.25

Cut: Maximum Flush



[Click to Enlarge](#)

7145E ★★★★★

Cutter - Tapered Head - Optimum Flush

5 7/8" Five Star***** Tapered Head optimum flush cutter. Made in the U.S.A. The 7100 series cutters have 1" longer Ergonomic handles and ESD safe foam cushion grips, stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell. Cutting range 20 AWG (.032") to 44 AWG (.002") soft copper leads and wires.
Length: 5.5
Cut: Optimum Flush



[Click to Enlarge](#)

7245E ★★★★★

Cutter - Tapered Head - Optimum Flush

4 7/8" Five Star***** Tapered Head optimum flush cutter. Made in the U.S.A. Cutting range 20 AWG (.032") to 30 AWG (.010") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell
Length: 5
Cut: Optimum Flush



[Click to Enlarge](#)

7143E ★★★★★

Cutter - Tapered Head - Semi Flush

5 7/8" Five Star***** Tapered Head semi flush cutter. Made in the U.S.A. The 7100 series cutters have 1" longer Ergonomic handles and ESD safe foam cushion grips, stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell. Cutting range 18 AWG (.040") to 32 AWG (.008") soft copper leads and wires.
Length: 5.5
Cut: Semi Flush



[Click to Enlarge](#)

7243E ★★★★★

Cutter - Tapered Head - Semi Flush

4 7/8" Five Star***** Tapered Head semi flush cutter. Made in the U.S.A. Cutting range 18 AWG (.040") to 28 AWG (.012") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell
Length: 5
Cut: Semi Flush



[Click to Enlarge](#)

7148E ★★★★★

Cutter - Tapered/Relieved - Optimum Flush

5 7/8" Five Star***** Tapered Relieved Head optimum flush cutter. Made in the U.S.A. The 7100 series cutters have 1" longer Ergonomic handles and ESD safe foam cushion grips, stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell. Cutting range 21 AWG (.028") to 44 AWG (.002") soft copper leads and wires.

Length: 5.5

Cut: Optimum Flush



[Click to Enlarge](#)

7146E ★★★★★

Cutter - Tapered/Relieved - Semi Flush

5 7/8" Five Star***** Tapered Relieved Head semi flush cutter. Made in the U.S.A. The 7100 series cutters have 1" longer Ergonomic handles and ESD safe foam cushion grips, stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell. Cutting range 19 AWG (.036") to 32 AWG (.008") soft copper leads and wires.

Length: 5.5

Cut: Semi Flush



[Click to Enlarge](#)

7147E ★★★★★

Cutter - Tapered/Relieved Head - Maximum Flush

5 7/8" Five Star***** Tapered Relieved Head maximum flush cutter. Made in the U.S.A. The 7100 series cutters have 1" longer Ergonomic handles and ESD safe foam cushion grips, stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell. Cutting range 19 AWG (.036") to 36 AWG (.005") soft copper leads and wires.

Length: 5.5

Cut: Maximum Flush



[Click to Enlarge](#)

7237E ★★★★★

Cutter - Tapered/Relieved Head - Maximum Flush

4 3/4" Five Star***** Tapered/Relieved Head maximum flush cut. Made in the U.S.A. Cutting range 20 AWG (.032") to 30 AWG (.010") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell.

Length: 4.75

Cut: Maximum Flush



[Click to Enlarge](#)

7247E ★★★★★

Cutter - Tapered/Relieved Head - Maximum Flush

4 7/8" Five Star***** Tapered/Relieved Head maximum flush cut. Made in the U.S.A. Cutting range 18 AWG (.040") to 30 AWG (.010") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell.

Length: 5

Cut: Maximum Flush



[Click to Enlarge](#)

76EI ★★★

Cutter - Tapered/Relieved Head - Maximum Flush

4" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 24 to 30 gauge. (.020" to .010")

Length: 4

Cut: Maximum Flush



[Click to Enlarge](#)

84EI ★★★

Cutter - Tapered/Relieved Head - Maximum Flush

4 3/4" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 20 to 28 gauge. (.032" to .012")

Length: 4.75

Cut: Maximum Flush



[Click to Enlarge](#)

92EI ★★★

Cutter - Tapered/Relieved Head - Maximum Flush

4 1/4" Maximum full flush precision lap joint cutter. Made in Italy from chrome vanadium tool steel. ESD safe foam cushion grips with stainless steel leaf springs. Cutting capacity 22 to 30 gauge. (.025" to .010")

Length: 4.25

Cut: Maximum Flush



[Click to Enlarge](#)

7237EH ★★★★★

Cutter - Tapered/Relieved Head - Maximum Flush for Hard Wire

4 3/4" Five Star***** Tungsten Alloy Hard Wire Cutters Our new Tungsten alloy cutters are designed for cutting many types of Stainless Steels, Nitinol, Elgiloy, and Tungsten. Made in the U.S.A. they come standard with our ESD safe molded teal Ergonomic grips and long lasting stainless steel leaf springs. 7237EH have "Maximum Flush" cutting blades.

Length: 4.75

Cut: Maximum Flush



[Click to Enlarge](#)

7248E ★★★★★

Cutter - Tapered/Relieved Head - Optimum Flush

4 7/8" Five Star***** Tapered/Relieved Head optimum flush cut. Made in the U.S.A. Cutting range 20 AWG (.032") to 30 AWG (.010") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell.

Length: 5

Cut: Optimum Flush



[Click to Enlarge](#)

7246E ★★★★★

Cutter - Tapered/Relieved Head - Semi Flush

4 7/8" Five Star***** Tapered/Relieved Head semi flush cut. Made in the U.S.A. Cutting range 18 AWG (.040") to 28 AWG (.012") soft copper leads and wires. Complete with new ESD safe teal Ergonomic grips. Long lasting stainless steel leaf springs. Made from 1% carbon tool steel hardened to 63/65 rockwell.

Length: 5

Cut: Semi Flush



[Click to Enlarge](#)

Product Search: