

infrastructure for a connected world

UNITED STATES | [CHANGE] | ENGLISH | REGISTER / LOG IN | FOLLOW US

PANDUIT

SOLUTIONS | PRODUCTS AND SERVICES | SUPPORT | ABOUT US

Search Panduit.com

GO

Search within category

GO

BUY NOW

DESIGN / INSTALL

FXURLE

NENXNM030

OM3 24-fiber, Interconnect, LSZH, 24F MPO Female to 24F MPO Female, Method A, Optimized IL, 30 m, Aqua.

Specs

Packaging Details

Documents

★ Add to Favorites

Add to BOM

|                        |                                                                                                                                           |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Application            | Data centers requiring quick infrastructure deployment with extended reach that want to maintain bandwidth throughout the infrastructure. |
| Assembly Length Range  | 30-39 m (98-130 ft)                                                                                                                       |
| Cable Color            | Aqua                                                                                                                                      |
| Connector 1 Type       | 24F MPO                                                                                                                                   |
| Connector 2 Type       | 24F MPO                                                                                                                                   |
| Fiber Count            | 24                                                                                                                                        |
| Fiber Type             | OM3                                                                                                                                       |
| Flammability Rating    | Low Smoke Zero Halogen (LSZH)                                                                                                             |
| Length (ft.)           | 98.43                                                                                                                                     |
| Length (m)             | 30.0                                                                                                                                      |
| Standards              | TIA/EIA-598-C.3, Plenum Rated NFPA-262, LSZH-Rated, Meet IEC-60332, RoHS Compliant                                                        |
| RoHS Compliancy Status | Compliant                                                                                                                                 |
| Min. Order Qty.        | 1.0000                                                                                                                                    |

LEGAL INFORMATION |

PRIVACY POLICY |

CONTACT US |

SITE MAP |

WHERE TO BUY |

JOBS |

UNSUBSCRIBE