



Main

Range of product	QO
------------------	----

Complementary

[Ue] rated operational voltage	208Y/120 V AC 240 V AC
AWG gauge	AWG 4...300 kcmil aluminium/copper
Maximum Depth	1.982 in (50.34 mm)
Maximum Height	5.06 in (128.52 mm)
Phase	3 phase
Number of spaces	18
Short-circuit protection	10 kA
Product compatibility	QO circuit-breaker
Product destination	QO circuit breaker QO-GFI circuit breaker QO-EPD circuit breaker
Maximum Width	8.014 in (203.56 mm)
Wiring configuration	3-wire

Environment

Product certifications	UL CSA
------------------------	-----------

Ordering and shipping details

Category	00909 - MOUNTING BASES, S/N
Discount Schedule	DE3A
GTIN	00785901868255
Package weight(Lbs)	3.23 lb(US) (1.47 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Circularity Profile	No need of specific recycling operations
Contractual warranty	
Warranty	18 months