



Flexible Conduits & Fittings

T&B Catalog Number:

UPC Number:
Status:
Description:

BVOD-P488GT
78620995297
Active

PMAFIX 90 degree black flange with seal and universal safety clip, material - polyamide 6, conduit size NW - 48.

Application

For cable protection systems in a wide range of applications

Characteristics

Very high impact resistance
Vibration proof connection to PMAFLEX conduits
High conduit pull-out strength
Easy installation, simply push the conduit in
Can be easily re-opened with a screwdriver
Free from halogens and cadmium
Fits both conduit profiles - Fine (T) and coarse (G)
Very good chemical properties
Selectable flange seal included

General

Material Polyamide 6
Color Black
Compatible With PMAFLEX, PMA Smart Line

Dimension Information

Fits to Conduit Size (NW) 48
Fits to Conduit Size (metric) 50
Fits to Conduit Size (inches) 1 1/2

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C
Technical Data Sheet Available on Website
Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating Up to IP66

Packaging

T&B Inner Pack 10
Package in Units 20
T&B Sold in UOM Each
T&B Weight Per UOM 0.33 lbs. Each

Application Support

PMA Reference Guide Available on Website
Product Overview-PMAFIX Connectors Available on Website
Available on Website

PMAFIX Connectors-Safety and Sealing
Systems

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com