Quareo™ Managed Copper Cables



Impedance matched for use in Quareo™ structured cabling systems, these managed cable exceed all performance requirements for Category 6 (Cat 6) and Augmented Category 6a (Cat 6a). The plug is designed with integrated strain relievers that prevent the cable from moving at the termination point when the cable is flexed, safeguarding circuit integrity and guaranteeing maximum performance. The strain relievers also ensure that proper bend radii are maintained throughout the network.



FEATURES

- Quareo Technology with connection point identification
- Connector Interface: Plug type RJ45 shielded/unshielded that conforms to 8 way modular RJ45 Jack according with IEC 60603-7 series and TIA/EIA-968-A.
- Latch Type: Snag-less
- Boot: Flexible with built in strain relief to maintain proper bend radius
- Wiring Configuration: T568A, T568B and T568A T568B (cross-over)



SPECIFICATIONS

ELECTRICAL

ANSI/TIA-568-C.2 and ISO 11801, Edition 2 for Category 6/Class E and Category 6a/Class EA Category 5e, 5 and 3 backward compatible

ENVIRONMENTAL

Controlled Environment GR-63, Section 4.1.2

Operating Temperature: -10° C to $+60^{\circ}$ C Storage Temperature: -0° C to $+50^{\circ}$ C

Relative Humidity: 5% to 90% non-condensing **Relative Humidity:** 5% to 95% non-condensing

COMPLIANCE

UL 94 V-0 TICK N355 C(UL)us 49S3

CE

RoHS and WEEE 2002/95/EC Directive on the restriction of the use of certain

hazardous substances in electrical and electronic equipment

ORDERING INFORMATION

Product Description	Available Colors Replace XX		ble Lengths place YY			Catalog Number
Category 6 U/UTP managed copper cable	BK = Black BL = Blue GN = Green OR = Orange RD = Red GY = Gray VT = Violet WT = White YL = Yellow	04' 07' 10' 01 m 03 m 7.5 m	15' 25' 50 02 m 05 m	PVC	T568A	QCPC-6RUVA-XXYYF
					T568B	QCPC-6RUVB-XXYYF
					Crossover	QCPC-6RUVX-XXYYF
				LSZH	T568A	QCPC-6RUZA-XXYYM
					T568B	QCPC-6RUZB-XXYYM
					Crossover	QCPC-6RUZX-XXYYM
Category 6a U/UTP managed copper cable				PVC	T568A	QCPC-6ARUVA-XXYYF
					T568B	QCPC-6ARUVB-XXYYF
					Crossover	QCPC-6ARUVX-XXYYF
				LSZH	T568A	QCPC-6ARUZA-XXYYM
					T568B	QCPC-6ARUZB-XXYYM
					Crossover	QCPC-6ARUZX-XXYYM
Category 6a F/UTP managed copper cable	BL = Blue GY = Gray WT = White	04' 07' 10'	15' 25' 50'	PVC	T568A	QCPC-6ARFVA-XXYYF
					T568A	QCPC-6ARFVB-XXYYF
					Crossover	QCPC-6ARFVX-XXYYF

DATA SHEET



Contact us:

Greensboro, NC USA 27409-8420 Tel: 800-366-3891, ext. 73347 Tel: 952-917-3347 (outside the US) Fax: 952-917-3237

www.te.com/adc

TE Connectivity, TE connectivity (logo), Tyco Electronics, TE (logo), and Quareo are trademarks of the TE Connectivity Ltd. family of companies and its licensors.

While TE Connectivity has made every reasonable effort to ensure the accuracy of the information in this document, TE Connectivity does not guarantee that it is error-free, nor does TE Connectivity make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE Connectivity reserves the right to make any adjustments to the information contained herein at any time without notice. TE Connectivity expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE Connectivity for the latest dimensions and design specifications.