Rittal - The System.

Faster – better – everywhere.

Hygienic DesignCompact enclosureHD – HD 1302.600

Date: Mar 19, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Hygienic Design Compact enclosure HD - HD 1302.600

created: 19.03.2018 build on www.rittal.com/us-en



Version: Roof slope 30° towards the front

Material: Housing and door: Stainless steel 1.4301 (AISI 304)

Mounting plate: Carbon steel

Lock inserts HD: Stainless steel 1.4404 (AISI 316L)

Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600

Surface finish: Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 μm

Mounting plate: Zinc-plated Seal: Blue, dyed (RAL 5010)

Protection category IP to IEC 60 529:

IP 66

Protection category IP to DIN 40 050-9:

IP 69K

Protection category

NEMA:

NEMA 13 NEMA 4X

Supply includes: Housing of all-round solid construction

Door with fitted seal

Door catch on right, may be swapped to the left

Mounting plate

Base material: Stainless steel

Product features

Dimensions: Height (front): 350 mm (14 ")

Height (rear): 437 mm (17 ")

Width: 220 mm (8.7 ")

© Rittal 2018

Depth: 155 mm (6.1 ")

Mounting plate:	Height: 275 mm (11 ") Width: 162 mm (6.4 ")
Number of cam locks:	1
Packaging unit:	1 pc(s).
Weight/packaging unit:	6.6 kg (14.6 lb.)
EAN:	4028177567597
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
e Cl@ss 8.0/8.1:	27180101
e Cl@ss 7.0/7.1:	27180101
e Cl@ss 6.0/6.1:	27180101
e Cl@ss 5.1/5.1.4:	27180102
Product description (long):	HD Compact enclosure, WHD: 220x350(H1)x437(H2)x155 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal
Approvals	
Approvals:	UL + C-UL
Certificates:	DGUV EAC
Declarations:	Declaration of conformity

© Rittal 2018 2