

XLR LOCKING 5 PIN CONNECTOR

GOLD PLATED CONTACTS

Io Audio Technologies' 5 pin XLR connectors showcase sleek black metal housing that allows for excellent RF protection. Precision machined, one piece, gold plated contacts are standard. Available in Male or Female variations, all with solder connections.





SPECIFICATION

Gender: Male, Female

Capacitance Between Contacts: ≤ 2pF

 Capacitance Between Contacts and Ground: ≤ 2pF

Contact Resistance: < 7mΩ

Insulation Resistance: ≥ 5000MΩ

Dielectric Strength: 1500V @ 60s

Rated Current/Voltage: 7.5A/125V AC


Lifetime: > 1000 mating cycles

Contact Plating: .05µm Au


Wiring: Solder Contacts


Drawings

IO-XLR5-M-BKAU



IO-XLR5-F-BKAU







FEATURES

Io Audio Technologies' 5 pin XLR connectors feature sturdy die-cast shells and gold plated contacts offering a durable connection. Their compact design includes a hard plastic insert that serves as a primary strain relief by clamping onto the cable jacket while the black rubber boot protects the junction from excessive bending. These 5 pin XLR connectors are also available in a silver plated variation (IO-XLR5-X-BK).

APPLICATIONS

5 pin XLR connectors are a perfect solution for applications requiring a rugged and dependable locking connection. Because the housing construction is threaded, the connectors require no tools for assembly, making them ideal for onsite termination and allow the user to be able to troubleshoot connection issues quickly. This connector is perfect for use in balanced audio, DMX, low voltage power, and control applications.

INDUSTRIES

- Pro Audio Manufacturing
- Pro Video Manufacturing
 Electronics Hobbyists
- Pro Lighting Manufacturing
 Medical Instruments
- Communications

PART NUMBER BREAKDOWN:

STANDARDS & CLASSIFICATIONS

IO-XLR5-M-BKAU Series Identifier

IO-XLR<u>5</u>-M-BKAU Number of Pins

IO-XLR5-M-BKAU Gender

IO-XLR5-M-BKAU BK = Black Housing Color

IO-XLR5-M-BKAU **Gold Contacts**



