

Model #: SS7415-15

Tripp Lite Power Strip with Surge Suppression - Multiple outlets wherever you need them

Highlights

- 16 outlets
- 15-ft. cord
- 48-in. length
- 450-joule rating



Description

The SS7415-15 4-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 16 NEMA 5-15R output receptacles with 2.717-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 450 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray housing with black output receptacles.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 16 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 4-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 450 joules

Applications

• Offers outlet power distribution with surge suppression for multiple loads in equipment racks, computer rooms, workbenches and raceways in a variety of internetworking, telecommunications, audio/video and live sound applications.

Package Includes

- SS7415-15 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

Specifications

| OVERVIEW | |
|----------------------|---|
| Intended Application | Computer Networking, Industrial/Factory Floor |
| SYSTEM OVERVIEW | |

| Voltage compatibility | 120V AC | |
|--------------------------------------|---|--|
| OUTPUT | | |
| Frequency compatibility | 50 / 60 Hz | |
| Output watts | 1800 | |
| Output volt amp capacity (amps) | 15A | |
| Outlet quantity / type | 16 NEMA 5-15R | |
| Outlet spacing | 2.717-in. center-to-center spacing | |
| INPUT | | |
| Recommended Electrical Service | 120V | |
| Input connection type | NEMA 5-15P | |
| Input cord length (ft.) | 15-ft. | |
| Input cord length (m) | 4.6 | |
| LEDS ALARMS & SWITCHES | | |
| Switches | Lighted 2-position power switch controls power to all outlets | |
| Locking switch cover | Transparent locking switch cover | |
| SURGE / NOISE SUPPRESSION | | |
| AC suppression joule rating | 450 joules | |
| UL1499 let through rating | | |
| DATALINE SURGE SUPPRESSION | | |
| Telephone/DSL Protection | No | |
| Cable (Coax) Protection | No | |
| Network (Ethernet) Protection | No | |
| PHYSICAL | | |
| Unit Dimensions (HWD/in) | 48 x 1.5 x 1.5 | |
| Mounting accessories included | Set of adjustable mounting clamps | |
| Receptacle Color | Black | |
| AC line cord color | Black | |
| CERTIFICATIONS | | |
| UL1449 1998 Rev. (AC Suppression) | UL1449 | |
| UL1363 (Power Tap) | UL1363 | |
| cUL / CSA (Canada) | cUL | |
| WARRANTY | | |
| Standard warranty period | Lifetime | |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=1948.

© 2010 Tripp Lite. All Rights Reserved.