## Product Ident BGUK 2

# **Enclosure Datasheet**



## **Identification**

Type Designation	e Designation BGUK 2		Sheet Metal	
Series BGUK		Color	RAL 5008	

## **Applications**

IP20 rated universal enclosure

#### **Standards**

IEC/EN 60529	IP20	
(please contact factory for higher IP Rating)		

2: Protected against solid objects > 50mm (e.g. Hands)

0: No Protection

2

## **Operation**

NEMA - Rating

Mounting				
Max. Power Losses inside				

Wall


17 W


## **Openings**


Wire feed though opening [inch]

0.2 - 0.40

#### **Dimensions**







	Outer Dimensions											
	А	В	С	D	E	F	G	Н	I	J	К	Drill
US [inch]	7.87	6.29	7.09	6.63	7.48	5.91	4.98	0.98	-	ı	-	0.18
	Inner Dimensions		Weight									
	Hight	Width	Deepth	we	igiit							
US [in ab ]	7.68	5.91	5.91	5.94 lbs								

### **Notes**

[inch]

Technical specifications in the drawing are not binding. General tolerance to DIN 7168-m. Subject to change.

Variations may apply due to material's and production's tolerances. Objected to modifications without notice.

Original Date:	7/23/2015
Name:	V. Wenzel
Date:	7/23/2015
Checked:	C. Wesner

Observe	protection	clause	to	ISO	16016
ODSCI VC	protection	Clause	ιU	100	TOOTO

Index	0		
Doc. type	Datasheet		
Pages	1 of 1		