



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PS-410-HGOEMCC

For Patient-Care Areas - 4-outlet Medical-Grade Power Strip with 3-ft. Coiled Cord (Extends to 10 Feet)

Highlights



- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- Tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 4 hospital-grade receptacles and hospital-grade plug
- 3-ft coiled cord, extends to 10-ft.
- Two 15-amp resettable circuit breakers

Description

Tripp Lite's PS-410-HG-OEMCC Power Strip is designed to be installed on any mobile cart, diagnostic equipment, instrument, IV pole, etc. It is TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack, table or pedestal-mounted. Features 4 output receptacles, 3-ft. AC coiled cord (extends to 10-ft.) and two built-in resettable circuit breakers that control power to all outlets and protect against overloads. Switchless design prevents accidental shutoff. Optional -use keyhole mounting tabs and flanges.
PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 4 NEMA5-15R-HG hospital-grade receptacles
ELECTRICAL: 120V AC, 50/60Hz, 15A
FORMAT: All-metal coil corded multi-outlet strip.

Applications

- Mobile carts, IV poles and other UL 1363A certified usages.
- Can be used in Patient Care Areas, when properly mounted.

Package Includes

- PS-410-HGOEMCC Power Strip
- Owner's manual and warranty information

Features

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 4 x NEMA 5-15R-HG hospital-grade output receptacles
- 3-ft. AC coiled cord (extends to 10-ft.) with integrated, molded NEMA5-15P-HG hospital-grade plug
- Rugged all-metal housing withstands years of use without breakage
- 15A electrical capacity with two built-in resettable circuit breakers
- 120V, 50/60Hz
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff

Specifications

OVERVIEW	
Intended Application	Hospital/Medical

Model Type	For Patient-Care Areas
OUTPUT	
Frequency compatibility	50 / 60 Hz
Circuit Breaker (amps)	15
Overload protection	2 x 15amp breakers (1 line, 1 neutral)
Outlet quantity / type	4 NEMA 5-15R-HG
Outlet orientation	Single row of 4
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A, 120V
Input connection type	NEMA 5-15P-HG
Input cord length (ft.)	10
Input cord length (m)	4.572
Input cord gauge, type	14 gauge, SJT
Voltage compatibility (VAC)	120
LEDS ALARMS & SWITCHES	
Switches	No power switch
PHYSICAL	
Shipping Dimensions (HWD/in)	2.44 x 6.18 x 9.92
Shipping Dimensions (HWD/cm)	6.19 x 15.7 x 25.2
Shipping weight (lbs)	2.4
Shipping weight (kg)	1.09
Unit Dimensions (HWD/in)	1.73 x 2.50 x 8.54
Unit Dimensions (HWD/cm)	4.39 x 6.35 x 21.69
Unit weight (lbs)	2.2
Unit weight (kg)	1.0
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Receptacle Color	White
AC line cord color	White
Style	Strip
Outlets center to center measurement	77.60mm

Keyhole slot center to center measurement	Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm
CERTIFICATIONS	
Approvals	TUV tested to UL 1363A
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
PSCLAMP	Power Strip Mounting Clamp	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4844.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.