

Rittal – The System.

Faster – better – everywhere.

Security lock – SZ 2418.000

Date : Mar 19, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Security lock – SZ 2418.000

created: 19.03.2018 build on www.rittal.com/us-en



Product description

Description:	Fitted to doors, to protect against contact with live electrical equipment while the master switch is ON.
Function principle:	Locks the door when the main switch is ON. Mains power (voltage) is only enabled whilst the door is closed. Monitoring of the lock magnet via an additional closing contact.
Mounting tip:	In the case of double-door enclosures, the door-operated switch is required for the overlapping door to indicate "enclosure door closed"
Supply includes:	Lock Actuator Angle bracket Fasteners

Product features

Rated operating voltage:	24 V (DC)
Power consumption:	with DC: 8 VA
Rated insulation voltage:	400 V AC
Rated impulse withstand voltage, phase to phase:	4000 V AC
Packaging unit:	1 pc(s).
Weight/packaging	0.74 kg (1.6 lb.)

unit:	
EAN:	4028177022690
Customs tariff number:	83015000
ETIM 6.0:	EC002626
ETIM 5.0:	EC002626
eCl@ss 8.0/8.1:	27189266
eCl@ss 7.0/7.1:	27189266
eCl@ss 6.0/6.1:	27189266
eCl@ss 5.1/5.1.4:	27189255
Product description (long):	SZ Security lock, 24 V DC
Approvals	
Approvals:	CSA UL
Certificates:	EAC
Declarations:	Declaration of conformity