



Displays

Short Form Catalog 2011

Liquid Crystal Displays

Full Line of Displays

- p-Si and a-Si Technology
- Small TFT Color Monitors
- Large and Medium TFT Color Modules
 - Intelligent LCD Graphic Displays
- Intelligent LCD Alphanumeric Displays
 - Panel/Segment Displays
- Film Super Twist Nematic
 - Super Twist Nematic

Precision Custom Enhancements:

- Anti-Reflective Films
- High-Bright Backlights
- White LED Backlights
 - Heaters
- Interface Cards
 - Inverters
 - Cabling

purdy®
ELECTRONICS
CORPORATION

755 North Pastoria Avenue
Sunnyvale, CA 94085-2918

Tel: 408.523.8200 Fax: 408.733.1287

Email: sales@purdyelectronics.com

www.purdyelectronics.com

LCD_SFC_0211



Color TFT Monitors (includes CCFL or LED backlight, inverter & control circuitry. *Control circuitry includes integrated DC-AC inverter to drive CCFL backlight.)

Part Number	Screen Diagonal (inches)	Pixel Count W x H	Brightness Nits (cd/m ²)	Pixel Pitch (mm) W x H	Active Area (mm) W x H	Overall Dimension (mm) W x H x D	Driving Voltage (V)	Input Signal
ANDpSi020TD-LED	2.0	320 x 240	250	0.053 x 0.159	40.67 x 30.48	46.1 x 40.96 x 2.53	12.0	NTSC, PAL
ANDpSi025TH-LED	2.5	320 x 240	250	0.053 x 0.159	50.91 x 38.16	61.7 x 44.5 x 2.68	12.0	NTSC, PAL
AND-TFT-25XS-LED	2.5	160 x 234	250	0.125 x 0.163	49.68 x 37.44	60.6 x 48.4 x 3.45	12.0	NTSC, PAL
AND-TFT-35VH-UHB-LED	3.5	640 x 480	1,500	0.1125 x 0.1095	72 x 52.56	84.24 x 65.4 x 3.45	5.0	VGA, NTSC, PAL
AND-TFT-35VX	3.5	640 x 480	210	0.1125 x 0.1095	72 x 52.56	84.24 x 65.4 x 3.45	5.0	VGA, NTSC, PAL
AND-TFT-35XS-LED	3.5	320 x 234	250	0.074 x 0.225	71.6 x 52.65	83.5 x 63.1 x 3.6	12.0	NTSC, PAL
AND-TFT-5PA	5.0	320 x 234	400	0.107 x 0.319	102.7 x 74.5	127 x 93 x 13	12.0*	NTSC, PAL
AND-TFT-5PA-DHB	5.0	320 x 234	500	0.32 x 0.32	102.7 x 74.5	127 x 93 x 13	12.0*	NTSC, PAL
AND-TFT-5VX	5.0	640 x 480	400	0.156 x 0.159	74.88 x 101.76	91.4 x 119.3 x 7.9	12.0	VGA, NTSC, PAL
AND-TFT-5VX-4HB	5.0	640 x 480	1,000	0.156 x 0.159	74.88 x 101.76	91.4 x 119.3 x 7.9	12.0	VGA, NTSC, PAL
AND-TFT-64PA	6.4	320 x 234	330	0.135 x 0.416	129.6 x 97.3	156.3 x 120 x 14.3	12.0*	NTSC, PAL
AND-TFT-64PA-DHB	6.4	320 x 234	500	0.135 x 0.416	129.6 x 97.3	156.3 x 120 x 14.3	12.0*	NTSC, PAL
AND-TFT-7WX	7.0	480 x 234	400	0.190 x 0.190	152.4 x 91.44	165 x 104 x 6.2	12.0	NTSC, PAL

Color TFT Modules (includes CCFL or LED backlight)

Part Number	Screen Diagonal (inches)	Pixel Count ⁽¹⁾ W x H	Brightness Nits (cd/m ²)	Pixel Pitch (mm) W x H	Active Area (mm) W x H	Overall Dimension (mm) W x H x D	Driving Voltage (V)	Input Signal ⁽²⁾
AND050VL-LED	5.0	640 x 480	450	0.159 x 0.156	101.76 x 74.88	120.7 x 92.8 x 12.5	5.0	LVDS 6-bit interface
ANDpSi056ET0S-HB	5.6	1024 x 600	250	0.120 x 0.120	122.88 x 72	141.8 x 84.4 x 7.5	3.3	LVDS 6-bit interface
ANDpSi056ET0S-LED	5.6	1024 x 600	400	0.120 x 0.120	122.88 x 72	141.8 x 84.4 x 7.5	5.0	LVDS 6-bit interface
ANDpSi064VT-HB-LED	6.4	640 x 480	400	0.203 x 0.203	129.6 x 97.44	175.4 x 126.9 x 12.5	5.0	LVDS 6-bit interface
AND065A041F-HB2	6.5	640 x 480	400	0.207 x 0.207	132.48 x 99.36	153 x 118 x 11	5.0	Digital 6-bit interface
AND-TFT-070WL3	7.0	800 x 480	400	0.1905 x 0.1905	152.4 x 91.44	166.3 x 105.3 x 10.7	3.3	Digital 6-bit interface
ANDpSi08C351-HB	8.4	800 x 600	350	0.213 x 0.213	170.4 x 127.8	200 x 150 x 12	12.0	NTSC, PAL
ANDpSi089C362S	8.9	1024 x 600	250	0.1905 x 0.1890	195.07 x 113.4	219.5 x 134.5 x 5.2	3.3	Digital 6-bit interface
ANDpSi089C362S-4HB	8.9	1024 x 600	800	0.1905 x 0.1890	195.07 x 113.4	219.5 x 134.5 x 8.4	3.3	LVDS 6-bit interface
ANDpSi104EA5S-HB	10.4	1024 x 768	180	0.2055 x 0.2055	210.4 x 157.8	242 x 172 x 6	3.3	LVDS 6-bit interface
ANDpSi104EA5S-LED	10.4	1024 x 768	1,000	0.2055 x 0.2055	210.4 x 157.8	237.7 x 173.2 x 14.6	3.3	LVDS 6-bit interface
AND12C285-DHB	12.1	800 x 600	500	0.3075 x 0.3075	246.0 x 184.5	290 x 220 x 15	5.0	Digital 6-bit interface
AND12C285-4HB	12.1	800 x 600	850	0.3075 x 0.3075	246.0 x 184.5	290 x 209 x 12	5.0	Digital 6-bit interface
ANDpSi121GA0S	12.1	1024 x 768	350	0.24 x 0.24	246.0 x 184.5	278 x 209 x 12	3.3	LVDS 6-bit interface
ANDpSi121C250F-HB	12.1	1024 x 768	400	0.24 x 0.24	246.7 x 184.32	278.3 x 209 x 12	3.3	LVDS 6-bit interface

Note 1: VGA = 640 x 480 resolution; SVGA = 800 x 600 resolution; XGA = 1024 x 768 resolution

Note 2: 6-bit = 256K colors; 8-bit = 16.2 M colors



Monochromatic Displays

Intelligent Graphic Displays (STN, FSTN, BST) Note 1: Wide Viewing angle display

Part Number	Pixel Count W x H	Pixel Pitch (mm) W x H	Viewing Area (mm) W x H	Overall Dimension (mm) W x H x D	Driving Voltage(V)	Built-in Controller	Backlight -30 -EL	Contrast Ratio
AND1264GST-LED	128 x 64	0.56 x 0.52	72 x 40	87 x 70 x 12.7	+5	T6963C	LED	7:1
AND1264WGST-LED	128 x 64	0.56 x 0.52	72 x 40	87 x 70 x 12.7	+5	T6963C	LED	7:1
AND1391ST	128 x 128	0.43 x 0.43	62 x 62	84.4 x 100 x 14	+5/-14.5	T6963C		4:1
AND1391ST-EO	128 x 128	0.43 x 0.43	62 x 62	84.4 x 100 x 14	+5/-14.5	T6963C	EL	4:1
AND1013ST-30	160 x 128	0.60 x 0.60	101 x 82	129 x 104.5 x 14	+5/-8.5	T6963C	-30	4:1
AND1013ST-EO	160 x 128	0.60 x 0.60	101 x 82	129 x 104.5 x 14	+5/-8.5	T6963C	EL	4:1
AND711AST-30	240 x 64	0.53 x 0.53	132 x 39	180 x 65 x 12	+5/-8.5	T6963C	-30	4:1
AND711AST-EO	240 x 64	0.53 x 0.53	132 x 39	180 x 65 x 12	+5/-8.5	T6963C	EL	4:1
AND1781BST	240 x 64	0.53 x 0.53	127.2 x 33.9	180 x 70 x 14	+5/-12.2	T6963C	CCFL	6:1
AND1781BST-LED	240 x 64	0.53 x 0.53	134 x 40.4	180 x 65 x 9.7	+5	T6963C	LED	6:1
AND1781MST-LED	240 x 64	0.53 x 0.53	127.2 x 33.9	180 x 70 x 14	+5	T6963C	LED	12:1
AND1743MST-LED	240 x 64	0.50 x 0.50	132 x 76	170 x 95 x 14	+5	T6963C	LED	6:1
AND1743FST-LED	240 x 128	0.50 x 0.50	132 x 76	170 x 95 x 14	+5	T6963C	LED	6:1
AND1742MST2	240 x 128	0.51 x 0.51	134 x 76	180 x 110 x 15.1	+5	RAIO	CCFL	6:1
AND322MST2	320 x 240	0.36 x 0.36	120 x 92	148 x 120 x 20.5	+5/-22.0	SED1335	CCFL	6:1
AND322MST2-LEDW ⁽¹⁾	320 x 240	0.36 x 0.36	120.14 x 92.14	148 x 120 x 20.5	+5	SED1335	LED White	6:1

Intelligent Alphanumeric STN Displays

Part Number	Lines x Characters	Character Size (mm) W x H	Viewing Area (mm) W x H	Outline Dimension (mm) W x H x D	Driving Voltage (V)	Built-in Con- troller	Backlight
AND081GST	1 x 8	4.45 x 8.35	48.0 x 13.0	60 x 36 x 10	5	HD44780	-
AND081GST-LED	1 x 8	4.45 x 8.35	48.0 x 13.0	60 x 36 x 13	5	HD44780	LED
AND082GST	2 x 8	2.96 x 5.56	38.0 x 16.0	58 x 32 x 8.4	5	HD44780	-
AND082GST-LED	2 x 8	2.96 x 5.56	38.0 x 16.0	58 x 32 x 12.8	5	HD44780	LED
AND671GST	1 x 16	3.07 x 6.56	64.5 x 13.8	80 x 36 x 11.3	5	HD44780	-
AND671GST-LED	1 x 16	3.07 x 6.56	64.5 x 13.8	80 x 36 x 16	5	HD44780	LED
AND471GST	2 x 16	4.84 x 9.66	99 x 24	122 x 44 x 11.3	5	HD44780	-
AND471GST-LED	2 x 16	4.84 x 9.66	99 x 24	122 x 44 x 15.8	5	HD44780	LED
AND481GST	2 x 16	2.78 x 4.89	62 x 16	85 x 30 x 10.1	5	HD44780	-
AND481GST-LED	2 x 16	2.78 x 4.89	62 x 16	85 x 30 x 15.8	5	HD44780	LED
AND491GST	2 x 16	2.95 x 4.35	64.5 x 13.8	80 x 36 x 11.3	5	HD44780	-
AND491GST-LED	2 x 16	2.95 x 4.35	64.5 x 13.8	80 x 36 x 15.8	5	HD44780	LED
AND731GST	4 x 16	2.95 x 4.75	62 x 25.6	87 x 60 x 8.8	5	HD44780	-
AND731GST-LED	4 x 16	2.95 x 4.75	62 x 25.6	87 x 60 x 12.7	5	HD44780	LED
AND501GST	2 x 20	3.2 x 5.55	83 x 18.6	116 x 37 x 11.3	5	HD44780	-
AND501GST-LED	2 x 20	3.2 x 5.55	83 x 18.6	116 x 37 x 15.8	5	HD44780	LED
AND501WGST	2 x 20	3.2 x 5.55	83 x 18.6	116 x 37 x 15.8	5	HD44780	-
AND501WGST-LED	2 x 20	3.2 x 5.55	83 x 18.6	116 x 37 x 15.8	5	HD44780	LED
AND721GST	4 x 20	2.95 x 4.75	76 x 25.2	98 x 60 x 12	5	HD44780	-
AND721GST-LED	4 x 20	2.95 x 4.75	76 x 25.2	98 x 60 x 16	5	HD44780	LED
AND771GST	2 x 24	3.2 x 5.50	94.5 x 17.8	118 x 36 x 11.3	5	HD44780	-
AND771GST-LED	2 x 24	3.2 x 5.50	94.5 x 17.8	118 x 36 x 15.8	5	HD44780	LED
AND591GST	2 x 40	3.2 x 5.55	154 x 15.3	182 x 33.5 x 8.8	5	HD44780	-
AND591GST-LED	2 x 40	3.2 x 5.55	154 x 15.3	182 x 33.5 x 12.7	5	HD44780	LED
AND791GST	4 x 40	2.78 x 4.89	149 x 29.5	190 x 54 x 8.8	5	HD44780	-
AND791GST-LED	4 x 40	2.78 x 4.89	149 x 29.5	190 x 54 x 13	5	HD44780	LED

Purdy Electronics Corporation • 755 North Pastoria Avenue • Sunnyvale, CA 94085-2918

Tel: 408.523.8200 • Fax: 408.733.1287 • Email: sales@purdyelectronics.com • www.purdyelectronics.com

**Notes for the Intelligent Graphic Displays**

- "30" means that the LCD has a transfective reflector. Part would be ordered with a "-30" suffix (i.e. AND1013ST-30)
- "EO" means that an electroluminescent panel is installed in the LCD. Order with the "EO" suffix (i.e. AND1013ST-EO)
- CCFL means that a cold cathode fluorescent lamp is installed in the module.
- "MST" means Film Super Twist Nematic (FSTN)
- "BST" means Blue Mode Super Twist Nematic LCD

LCD - Panel-Segment Displays (Wide Temperature & High Humidity)

Part Number	Display Font	Digit Height in inches	Package Dimensions in inches (Length x Width)
FE1901W		0.5	1.1 x 1.2
FE0201W		0.5	2.0 x 1.2
FE0203W		0.5	2.0 x 1.2
FE0202W		0.5	2.0 x 1.2
FE0501W		0.7	2.75 x 1.5
FE0502W		0.7	2.75 x 1.5
FE0206W		0.5	2.0 x 1.2
FE0208W		0.4	2.0 x 1.2
FE0401W		0.5	2.75 x 1.2
FE0601W		0.7	3.7 x 1.5
FE1001W		0.5	3.7 x 1.2

Backlight viewing mode designation is:

- DU for "reflective" surface to reflect ambient light back through the liquid crystal materials for illumination.
- EU for "transfective" surface which uses a partially reflecting surface for viewing with a backlight or using reflected light.
- Example: To receive a 0.5-inch high, 4-digit, wide temperature, high humidity, reflective panel display, order: FE202+w-DU = FE0202W-DU

Purdy Electronics
The Design Engineer's Source for High Quality Component Solutions

The mission of Purdy Electronics Corporation is to provide our original equipment manufacturer (OEM) customers with the highest quality electronic components at competitive prices, supported with superior customer service and technical service and value-added enhancements.

Purdy Electronics has been providing electronic components to OEMs for over 75 years. We specialize in manufacturing a limited number of product lines including:

