



For full product information, visit www.sti.com. Use the SpeedSpec Code or scan the QR Code for quick access to the specific web page.

Mini Contactor Relays 4-Pole

- AC and DC operated
- 4-, 6- and 8-pole versions in different configurations
- Mirrored contacts
- Screw fixing and snap fitting (35 mm DIN rail)
- Rated current = 10A (I_{th})
- Suitable for electronic devices (DIN 19240)
- Finger proof (VBG 4)
- A Rapid Delivery Product: Select models are available for shipment today or within 3 to 5 days

Accessories

- 2- and 4-pole additional auxiliary contacts in different configurations



Specifications

Electrical	
Operating Coil	
Supply Power:	24 VDC, 110 VAC or 230 VAC
Inrush:	25 VA for AC versions 3 W for DC versions
Power Usage:	4.5 VA for AC versions 2.5 W for DC versions
Rated Carry Current:	10 A @ 40C
Switching Capability Inductive Loads (AC-15, DC-13)	
AC:	Break 120 V - 6 A, 240 V - 3 A (continuous 10 A)
DC:	24 V - 3 A
Max. Switching Frequency:	10,000 per hour
Min. Switching Current:	5 mA
Max. Drop-Out Time*:	8-25 ms for AC versions 8-25 ms for DC versions
Mechanical	
Mechanical Life:	1 x 10 ⁷ operations min.
Mounting:	35 mm DIN rail or 4 screw holes for panel mounting
Wire Size:	Screw terminals accept two 14 AWG solid or stranded wires
Weight:	AC versions: 160 g (5 oz.) DC versions: 190 g (6 oz.)
Vibration:	5 to 300 Hz
Environmental	
Vibration Resistance:	2 g with control relay open; 4 g with control relay closed
Operating Temperature:	-40 to 60°C (-40 to 140°F)
Approvals:	IEC947-5-1, VDE 0660, EN60947-5-1, UL508

*The Drop-Out Time is the time it takes for the N/O contacts to open after the coil voltage is turned OFF.
Specifications are subject to change without notice.

Approved Standards

Standard	Guide No. (US,C)
UL	NKCR, NKCR7
ICE 947-5-1	
VDE 0660	
EN 60947-5-1	

 **Select models are available for Rapid Delivery.**


Visit this product on www.sti.com for details..

Dimensions

(mm)


AC and DC Operated with Screw Terminals

J7KNA-AR



Auxiliary Contact Blocks


J73KN-A




Contact Diagrams

Mini Contactor Relays, 4-Pole


J7KNA-AR-40



J7KNA-AR-31



J7KNA-AR-22




Auxiliary Contact Blocks for Contactor Relays J7KNA-AR


J73KN-A-11




J73KN-A-02



J73KN-A-40



J73KN-A-22



 Select models are available for Rapid Delivery.

Visit this product on www.sti.com for details..


Mirror Contacts

Safety Function with Mirror Contacts

EN 60947-4-1 certification for mirror contact mechanisms has been obtained by using a combination of a relay and auxiliary contact blocks (5 VDC, 1 mA), enabling application in feedback circuits of safety circuits.


Application Example: General Safety Circuit

G9SA-301 (24-V AC/DC) (two limit switch input channels with manual reset)



Mirror Contact Mechanism

By combining a Relay with an auxiliary contact block, all NC contacts of the auxiliary contact block will satisfy an impulse withstand voltage of 2.5 kV or higher or maintain a gap of 0.5 mm or greater when the coil is de-energized even if at least one NO contact (main contact) of the Relay is welded.



Select models are available for Rapid Delivery.

Visit this product on www.sti.com for details..

Ordering

Model Number Legend

Mini Contactor Relays

J7KNA – AR – □ – □

① ②

① Combination of NO/NC Contacts

22: 2 NO/2 NC

31: 3 NO/1 NC

40: 4 NO

② Coil Voltage (AC operated)

24: AC 24 V 50/60 Hz

110: AC 110-115 V 50 Hz, AC 120-125 V 60 Hz

230: AC 220-230 V 50 Hz, AC 240 V 60 Hz

Coil Voltage (DC operated)

24VS: 24 VDC with suppression

Auxiliary Contact Modules for Mini Motor Contactor Relays

J73KN – A – □

①

① Combination of NO/NC Contacts

11: 1 NO/1 NC

02: 2 NC

22: 2 NO/2NC

40: 4 NO

Model	Coil Voltage	Contacts	Part No.
AC Operated Relays			
J7KNA-AR-40 24	24 VAC	4 N/O	12010-4140
J7KNA-AR-31 24	24 VAC	3 N/O + 1 N/C	12010-4131
J7KNA-AR-22 24	24 VAC	2 N/O + 2 N/C	12010-4122
J7KNA-AR-40 110	110 VAC	4 N/O	12010-4240
J7KNA-AR-31 110	110 VAC	3 N/O + 1 N/C	12010-4231
J7KNA-AR-22 110	110 VAC	2 N/O + 2 N/C	12010-4222
J7KNA-AR-40 230	230 VAC	4 N/O	12010-4340
J7KNA-AR-31 230	230 VAC	3 N/O + 1 N/C	12010-4331
J7KNA-AR-22 230	230 VAC	2 N/O + 2 N/C	12010-4322
DC Operated Relays (coil suppression built -in)			
J7KNA-AR-40 24VS	24 VDC	4 N/O	12010-4040
J7KNA-AR-31 24VS	24 VDC	3 N/O + 1 N/C	12010-4031
J7KNA-AR-22 24VS	24 VDC	2 N/O + 2 N/C	12010-4022
Auxiliary Contact Modules			
J73KN-A-11		1 N/C + 1 N/O	12010-4411
J73KN-A-02		2 N/C	12010-4402
J73KN-A-40		4 N/O	12010-4440
J73KN-A-22		2 N/O + 2 N/C	12010-4422



Select models are available for Rapid Delivery.

Visit this product on www.sti.com for details..