

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

**Part Number:** [67068-9011](#)  
**Status:** **Active**  
**Overview:** [USB](#)  
**Description:** Universal Serial Bus (USB), Shielded I/O, Type B Receptacle, Right Angle with Straight Tabs, Color White, 0.76µm Gold (Au) Plating, Tray Pack, Lead-Free

**Documents:**  
[3D Model](#) [Product Specification PS-67998-0000 \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**


CSA LR19980  
UL E29179

**General**

Product Family I/O Connectors  
Series [67068](#)  
Application Wire-to-Board  
Comments Single  
Component Type Receptacle  
Overview [USB](#)  
Product Name USB  
Type B  
UPC 822348723034

**Physical**

Boot Color N/A  
Circuits (Loaded) 4  
Circuits (maximum) 4  
Flammability 94V-0  
Gender Receptacle  
Lock to Mating Part Yes  
Material - Plating Mating Gold  
Material - Plating Termination Tin  
Net Weight 3.466/g  
Number of Rows 2  
Orientation Right Angle  
PC Tail Length 2.80mm  
PCB Locator Yes  
PCB Retention Yes  
PCB Thickness - Recommended 1.60mm  
Packaging Type Tray  
Panel Mount No  
Pitch - Mating Interface 2.50mm  
Pitch - Termination Interface 2.50mm  
Plating min - Mating 0.762µm  
Plating min - Termination 1.905µm  
Polarized to Mating Part Yes  
Polarized to PCB Yes  
Ports 1  
Surface Mount Compatible (SMC) Yes  
Temperature Range - Operating 0°C to +50°C  
Termination Interface: Style Through Hole  
Waterproof / Dustproof No  
Wire Size AWG N/A



Series

image - Reference only

**EU RoHS**  
**ELV and RoHS**  
**Compliant**  
**REACH SVHC**  
**Contains SVHC: No**  
**Low-Halogen Status**  
**Not Low-Halogen**

**China RoHS**



**Need more information on product environmental compliance?**  
  
Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of Compliance, [click here](#)  
  
Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**  
[67068Series](#)

**Mates With**  
USB Type B Plug

**Electrical**

|                               |             |
|-------------------------------|-------------|
| Current - Maximum per Contact | 1.5A        |
| Shield Type                   | Full Shield |
| Shielded                      | Yes         |
| Voltage - Maximum             | 30V (RMS)   |

**Material Info**

**Reference - Drawing Numbers**

|                       |               |
|-----------------------|---------------|
| Product Specification | PS-67998-0000 |
| Sales Drawing         | SD-67068-003  |

This document was generated on 01/25/2013

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**