

Product availability: Stock - Normally stocked in distribution facility



## Main

|                                    |                                                                                                      |
|------------------------------------|------------------------------------------------------------------------------------------------------|
| Range of product                   | Altivar 12                                                                                           |
| Product or component type          | Variable speed drive                                                                                 |
| Product destination                | Asynchronous motors                                                                                  |
| Product specific application       | Simple machine                                                                                       |
| Assembly style                     | With heat sink                                                                                       |
| Component name                     | ATV12                                                                                                |
| Quantity per set                   | Set of 1                                                                                             |
| EMC filter                         | Without EMC filter                                                                                   |
| Built-in fan                       | Without                                                                                              |
| Phase                              | 3 phase                                                                                              |
| [Us] rated supply voltage          | 200...240 V - 15...10 %                                                                              |
| Motor power kW                     | 0.75 kW                                                                                              |
| Maximum Horse Power Rating         | 1 hp                                                                                                 |
| Communication port protocol        | Modbus                                                                                               |
| Line current                       | 6.3 A 200 V<br>5.3 A 240 V                                                                           |
| Speed range                        | 1...20                                                                                               |
| Transient overtorque               | 150...170 % of nominal motor torque depending on drive rating and type of motor                      |
| Asynchronous motor control profile | Sensorless flux vector control<br>Voltage/Frequency ratio (V/f)<br>Quadratic voltage/frequency ratio |
| IP degree of protection            | IP20 without blanking plate on upper part                                                            |
| Noise level                        | 0 dB                                                                                                 |

## Complementary

|                              |                                                                                                                                                                                                          |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply frequency             | 50/60 Hz +/- 5 %                                                                                                                                                                                         |
| Connector type               | 1 RJ45 on front face)Modbus                                                                                                                                                                              |
| Physical interface           | 2-wire RS 485 Modbus                                                                                                                                                                                     |
| Transmission frame           | RTU Modbus                                                                                                                                                                                               |
| Transmission rate            | 4800 bit/s<br>9600 bit/s<br>19200 bit/s<br>38400 bit/s                                                                                                                                                   |
| Number of addresses          | 1...247 Modbus                                                                                                                                                                                           |
| Communication service        | Read holding registers (03) 29 words<br>Write single register (06) 29 words<br>Write multiple registers (16) 27 words<br>Read/Write multiple registers (23) 4/4 words<br>Read device identification (43) |
| Prospective line Isc         | 5 kA                                                                                                                                                                                                     |
| Continuous output current    | 4.2 A 4 kHz                                                                                                                                                                                              |
| Maximum transient current    | 6.3 A 60 s                                                                                                                                                                                               |
| Speed drive output frequency | 0.5...400 Hz                                                                                                                                                                                             |
| Nominal switching frequency  | 4 kHz                                                                                                                                                                                                    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                                            |                                                                                                                                                                                                                                                                                                       |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switching frequency                        | 2...16 kHz adjustable<br>4...16 kHz with derating factor                                                                                                                                                                                                                                              |
| Braking torque                             | Up to 70 % of nominal motor torque without braking resistor                                                                                                                                                                                                                                           |
| Motor slip compensation                    | Preset in factory<br>Adjustable                                                                                                                                                                                                                                                                       |
| Output voltage                             | 200...240 V 3 phase                                                                                                                                                                                                                                                                                   |
| Electrical connection                      | Terminal 3.5 mm <sup>2</sup> , AWG 12 L1, L2, L3, U, V, W, PA, PC)                                                                                                                                                                                                                                    |
| Tightening torque                          | 7.08 lbf.in (0.8 N.m)                                                                                                                                                                                                                                                                                 |
| Insulation                                 | Electrical between power and control                                                                                                                                                                                                                                                                  |
| Supply                                     | Internal supply for reference potentiometer 5 V DC 4.75...5.25 V), <10 mA over-<br>load and short-circuit protection<br>Internal supply for logic inputs 24 V DC 20.4...28.8 V), <100 mA overload and<br>short-circuit protection                                                                     |
| Analogue input number                      | 1                                                                                                                                                                                                                                                                                                     |
| Analogue input type                        | Configurable current AI1 0...20 mA 250 Ohm<br>Configurable voltage AI1 0...10 V 30 kOhm<br>Configurable voltage AI1 0...5 V 30 kOhm                                                                                                                                                                   |
| Discrete input number                      | 4                                                                                                                                                                                                                                                                                                     |
| Discrete input type                        | Programmable LI1...LI4 24 V 18...30 V                                                                                                                                                                                                                                                                 |
| Discrete input logic                       | Negative logic (sink), > 16 V, < 10 V 3.5 kOhm<br>Positive logic (source), 0...< 5 V, > 11 V                                                                                                                                                                                                          |
| Sampling duration                          | 20 Ms +/- 1 ms logic input<br>10 ms analogue input                                                                                                                                                                                                                                                    |
| Linearity error                            | +/- 0.3 % of maximum value analogue input                                                                                                                                                                                                                                                             |
| Analogue output number                     | 1                                                                                                                                                                                                                                                                                                     |
| Analogue output type                       | AO1 software-configurable voltage 0...10 V 470 Ohm 8 bits<br>AO1 software-configurable current 0...20 mA 800 Ohm 8 bits                                                                                                                                                                               |
| Discrete output number                     | 2                                                                                                                                                                                                                                                                                                     |
| Discrete output type                       | Logic output LO+, LO-<br>Protected relay output R1A, R1B, R1C 1 C/O                                                                                                                                                                                                                                   |
| Minimum switching current                  | 5 mA 24 V DC logic relay                                                                                                                                                                                                                                                                              |
| Maximum switching current                  | 2 A 250 V AC inductive cos phi = 0.4 L/R = 7 ms logic relay<br>2 A 30 V DC inductive cos phi = 0.4 L/R = 7 ms logic relay<br>3 A 250 V AC resistive cos phi = 1 L/R = 0 ms logic relay<br>4 A 30 V DC resistive cos phi = 1 L/R = 0 ms logic relay                                                    |
| Acceleration and deceleration ramps        | Linear from 0 to 999.9 s<br>S<br>U                                                                                                                                                                                                                                                                    |
| Braking to standstill                      | By DC injection, <30 s                                                                                                                                                                                                                                                                                |
| Protection type                            | Line supply overvoltage<br>Line supply undervoltage<br>Overcurrent between output phases and earth<br>Overheating protection<br>Short-circuit between motor phases<br>Against input phase loss in three-phase<br>Thermal motor protection via the drive by continuous calculation of I <sup>2</sup> t |
| Frequency resolution                       | Analog input converter A/D, 10 bits<br>Display unit 0.1 Hz                                                                                                                                                                                                                                            |
| Time constant                              | 20 ms +/- 1 ms for reference change                                                                                                                                                                                                                                                                   |
| Marking                                    | CE                                                                                                                                                                                                                                                                                                    |
| Operating position                         | Vertical +/- 10 degree                                                                                                                                                                                                                                                                                |
| Height                                     | 5.63 in (143 mm)                                                                                                                                                                                                                                                                                      |
| Width                                      | 2.83 in (72 mm)                                                                                                                                                                                                                                                                                       |
| Depth                                      | 5.17 in (131.2 mm)                                                                                                                                                                                                                                                                                    |
| Net weight                                 | 1.76 lb(US) (0.8 kg)                                                                                                                                                                                                                                                                                  |
| Specific application                       | Commercial equipment                                                                                                                                                                                                                                                                                  |
| Variable speed drive application selection | Mixer Commercial equipment<br>Other application Commercial equipment<br>Ironing Textile                                                                                                                                                                                                               |
| Motor starter type                         | Variable speed drive                                                                                                                                                                                                                                                                                  |

## Environment

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electromagnetic compatibility         | Electrical fast transient/burst immunity test level 4 EN/IEC 61000-4-4<br>Electrostatic discharge immunity test level 3 EN/IEC 61000-4-2<br>Immunity to conducted disturbances level 3 EN/IEC 61000-4-6<br>Radiated radio-frequency electromagnetic field immunity test level 3 EN/IEC 61000-4-3<br>Surge immunity test level 3 EN/IEC 61000-4-5<br>Voltage dips and interruptions immunity test EN/IEC 61000-4-11 |
| Electromagnetic emission              | Radiated emissions environment 1 category C2 EN/IEC 61800-3 2...16 kHz shielded motor cable<br>Conducted emissions with additional EMC filter environment 1 category C2 EN/IEC 61800-3 4...12 kHz shielded motor cable <65.62 ft (20 m)<br>Conducted emissions with additional EMC filter environment 2 category C3 EN/IEC 61800-3 4...12 kHz shielded motor cable <65.62 ft (20 m)                                |
| Product certifications                | GOST<br>UL<br>NOM<br>CSA<br>C-Tick                                                                                                                                                                                                                                                                                                                                                                                 |
| Vibration resistance                  | 1 gn 13...200 Hz)EN/IEC 60068-2-6<br>1.5 mm peak to peak 3...13 Hz) - drive unmounted on symmetrical DIN rail - EN/IEC 60068-2-6                                                                                                                                                                                                                                                                                   |
| Shock resistance                      | 15 gn 11 ms EN/IEC 60068-2-27                                                                                                                                                                                                                                                                                                                                                                                      |
| Relative humidity                     | 5...95 % without condensation IEC 60068-2-3<br>5...95 % without dripping water IEC 60068-2-3                                                                                                                                                                                                                                                                                                                       |
| Ambient air temperature for storage   | -13...158 °F (-25...70 °C)                                                                                                                                                                                                                                                                                                                                                                                         |
| Ambient air temperature for operation | 14...104 °F (-10...40 °C) protective cover from the top of the drive removed<br>104...140 °F (40...60 °C) with current derating 2.2 % per °C                                                                                                                                                                                                                                                                       |
| Operating altitude                    | <= 3280.84 ft (1000 m) without<br>> 3280.84...9842.52 ft (> 1000...3000 m) with current derating 1 % per 100 m                                                                                                                                                                                                                                                                                                     |

## Ordering and shipping details

|                     |                                     |
|---------------------|-------------------------------------|
| Category            | 22042 - ATV12 DRIVE AND ACCESSORIES |
| Discount Schedule   | CP4B                                |
| GTIN                | 00785901910329                      |
| Package weight(Lbs) | 1.06 kg (2.33 lb(US))               |
| Returnability       | Yes                                 |
| Country of origin   | ID                                  |

## Offer Sustainability


|                            |                                                                                                                              |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                        |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                               |
| Mercury free               | Yes                                                                                                                          |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                          |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                      |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions

Drive without EMC Conformity Kit




Dimensions in mm

| b   | c     | H   |
|-----|-------|-----|
| 130 | 131.2 | 120 |

Dimensions in in.

| b    | c    | H    |
|------|------|------|
| 5.12 | 5.16 | 4.72 |

Drive with EMC Conformity Kit



Dimensions in mm


| c1 |
|----|
| 63 |

Dimensions in in.


| c1   |
|------|
| 2.48 |

## Mounting Recommendations

### Clearance for Vertical Mounting



### Mounting Type A




### Mounting Type B




Remove the protective cover from the top of the drive.

### Mounting Type C



Remove the protective cover from the top of the drive.


### Three-Phase Power Supply Wiring Diagram



- A1 Drive  
KM1 Contactor (only if a control circuit is needed)  
Q1 Circuit breaker


### Recommended Schemes

#### 2-Wire Control for Logic I/O with Internal Power Supply




- L1 : Forward  
L1• : Reverse  
A1 : Drive

#### 3-Wire Control for Logic I/O with Internal Power Supply




- L1 : Stop  
L2 : Forward  
L1• : Reverse  
A1 : Drive

#### Analog Input Configured for Voltage with Internal Power Supply




- (1) 2.2 kΩ...10 kΩ reference potentiometer  
A1 : Drive

## Analog Input Configured for Current with Internal Power Supply




(2) 0-20 mA 4-20 mA supply  
A1 : Drive

## Connected as Positive Logic (Source) with External 24 vdc Supply




(1) 24 vdc supply  
A1 : Drive

## Connected as Negative Logic (Sink) with External 24 vdc supply



(1) 24 vdc supply  
A1 : Drive

## Torque Curves



- 1 : Self-cooled motor: continuous useful torque (1)
  - 2 : Force-cooled motor: continuous useful torque
  - 3 : Transient overtorque for 60 s
  - 4 : Transient overtorque for 2 s
  - 5 : Torque in overspeed at constant power (2)
- (1) For power ratings  $\leq 250$  W, derating is 20% instead of 50% at very low frequencies.
- (2) The nominal motor frequency and the maximum output frequency can be adjusted from 0.5 to 400 Hz. The mechanical overspeed capability of the selected motor must be checked with the manufacturer.