Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'F6LE3-10BM6'**

**Your search criteria matched only one product, shown below**

## F6LE3-10BM6

- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Include color-specific keys with positive and negative keying features to visually and mechanically distinguish connections to prevent unauthorized mating with unlike keyed or non-keyed adapters
- Part of a complete keyed LC system that includes *Opti-Core*® Patch Cords and Pigtails, *OptiCam*® Pre-Polished Cam Connectors, *Opticom*® Fiber Adapter Panels (FAPs) and *Mini-Com*® Adapter Modules
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode patch cord
- Lifetime traceability of test data to a Q.C. number on each patch cord
- Highest quality flame retardant fiber optic cable with tight-buffered coating on each optical fiber

*Additional lengths and availability: Keyed LC patch cords and pigtails are available in 1m – 10m lengths in 1m increments, and 15m, 20m, and 30m lengths. For other lengths, contact Customer Service for actual lead times.*
*Additonal keyed colors include the following: G– Violet, H– Aqua, J– Rose, K– Slate, L– Brown, P– White, Q– Charcoal, R– Lavender, S– Peach, T– Steel Blue, V– Maroon and W– Mint.*

| | |
|---|---|
| Part Number | F6LE3-10BM6 |
| RoHS Compliancy Status | Compliant |
| Note | Intended for use in fixed installations which are outside the scope of RoHS. |
| Part Description | SC to keyed LC (keyed B- red) multimode,low smoke zero halogen,duplex patch cord, 1.6mm jacketed cable (one duplex SC connector on one end and one duplex (keyed B-red) LC connector on the other end) – 62.5/125?m. |
| Product Type | Keyed LC Patch Cords |
| Length (m) | 6 |
| Fiber Compatibility | 62.5/125?m |
| Fiber Cable Size | 1.6mm |
| Fiber Cable Type | Jacketed |
| Fiber Type | Multimode 62.5/125 |
| Connector 1 Type | SC Connector |
| Connector 2 Type | LC Connector - Keyed B (Red) |
| Flammability Rating | Low Smoke Zero Haloagen (LSZH) |
| Key Type and Color | Keyed B (Red) |
| Pricing Description | SC to LC (keyed B- red) 62.5µ m Duplex, LSZH, Patch Cord6M |
| Min. Order UOM | PC |
| Min. Order Qty. | 1 |
| BOM Qty. (# of Pkgs.) | 0 |
| Add to Favorite Product List | e |

**Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.**


Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy